

Austwide sales and rentals pty ltd

Sold by

TOP MOUNT S Series: SRT45-4

___ FEATURES / BENEFITS =__

DIGITAL TEMPERATURE CONTROL SYSTEM

Provides precise and constant temperature. This level of precision allows food products to remain fresh over an extended period of time.

High-Tech Monitor

The monitor digitally displays present cabinet temperatures. You can easily change the temperature by adjusting the thermostat.

Hot Gas Condensate System

Through Turbo Air's creative innovation, the condensate system surfaces have been specially treated to resist corrosion. This not only increases efficiency without the risk of refrigerant leakage from corrosion, but also prevents the overflow of condensate water.

■ EFFICIENT REFRIGERATION SYSTEM

Turbo Air's solid door reach-in's are designed with oversized and balanced refrigeration systems. CFC Free R-134A utilized for refrigerator and R-404A for freezer. These include efficient evaporators and condensers for faster cooling and greater efficiency.

■ AUTOMATIC EVAPORATOR FAN MOTOR DELAYS

Through stopping the evaporator fan when the refrigerator door opens, the circulation of hot, moist air into the refrigerator is prevented. This increases energy efficiency and lengthens the life of the compressor.

ADJUSTABLE, HEAVY DUTY, PE(POLYETHYLENE) COATED WIRE SHELVES

■ EXTERIOR & INTERIOR OF CABINET CONSTRUCTION

Stainless steel exterior (galvanized steel top, bottom and back) and stainless steel interior with AL inside walls and door liners. It guarantees the utmost in cleanliness and long product life. Unlike other companies' products, the sharp corners and edges have been rounded to reduce the risk of injury.

■ HIGH-DENSITY POLYURETHANE INSULATION

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

■ ERGONOMICALLY DESIGNED DOORS

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience.



| Model | Swing Door | Capacity (Liters) | Shelves | Compressor (HP) | Amps (A) | Net Weight (Kg) | L X D X H (mm) |
|---------|------------|----------------------|---------|--------------------|----------|--------------------|-------------------|
| SRT45-4 | 4 | 1210 | 6 | 1/3 | 3.5 | 142 | 1260 x 850 x 1926 |





TOP MOUNT S Series: SRT45-4

Model: SRT45-4

| SPEC SHEET | SRT45-4 | | |
|---------------------------------|---|--|--|
| Classification | Refrigerator | | |
| Cabinet Dimension (WxDxH mm) | 1260x850x1926 | | |
| Capacity (Liters) | 1210 | | |
| Inner Temperature | 1°C~8°C | | |
| Doors | 4 | | |
| Number of Shelves | 6 | | |
| Refrigent | R-134a | | |
| Compressor (Hp) | 1/3 | | |
| Cooling Type | Fan cooling type | | |
| Insulation Type | Polyurethane / Cyclopentane + CFC Free | | |
| Temperature Control Type | Digital | | |
| Amps (A) | 3.5 | | |
| Voltage (V/Hz/Ph) | 240V 50Hz 1Ph | | |
| Power (W) | 366 | | |
| Weight (Kg) | 142 | | |





